

Delock Converter HDMI > 3G-SDI

Description

This Delock converter can be used to convert an HDMI signal to an HD- or 3G-SDI signal. You can connect e. g. a camera with HDMI output to an HD-SDI recorder. The SDI signal is transmitted via a conventional 75 Ohm coaxial cable with BNC connectors.



Note

Inside the box there are pillars that need to be shortened when using larger Keystone modules. Details are shown in the technical drawing.

Special features

- Especially slim cable diameter

Specification

- Connector:
 - Input: 1 x HDMI-A female
 - Output: 2 x BNC female (2 x SDI, parallel)
- Chipset: GV7600
- Supports 3G-SDI Level A
- Supported resolution:
 - SD 480i, 525i and 625i
 - HD 720p 24, 25, 30, 50 and 60 Hz
 - HD 1080i 50, 60 Hz
 - HD 1080p 24, 25, 30, 50 and 60 Hz
- Supported data rate: 270 Mb/s ~ 2.97 Gb/s
- Supports 8 channels of 48 kHz PCM audio
- Robust metal housing
- Power consumption: max. 4 W
- Dimensions (LxWxH): ca. 100 x 70 x 25 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 9 mm

Specification of the power jack

- 5 V, ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 1.35 mm
 - outside: \varnothing ca. 3.5 mm
 - length: ca. 9.65 mm

Package content

Item No. 93238

EAN: 4043619932382

Country of origin: China

Package: White Box



- HDMI > 3G-SDI Converter
- Mounting brackets and screws
- Power supply

Images

