

# DESONO™ COLW101

## TWO-WAY 10 x 3.3-INCH COLUMN LOUDSPEAKER



### FEATURES

- Zoom Certified
- IP66 rated for outdoor applications such as patios or concourses
- High speech intelligibility coupled with full-range music reproduction
- Stylish yet subtle design; blends well in many environments
- Tap switch allows for 70V/100V or 16Ω low impedance operation

### TECHNICAL SPECIFICATIONS<sup>1</sup>

|  |   |                       |
|--|---|-----------------------|
| Operating Mode   | Passive   |                       |
| Operating Environment                                      | Indoor/Outdoor  |                       |
| Operating Range <sup>2</sup> (-10dB)                       | 165 Hz to 18 kHz  |                       |
| Nominal Beamwidth (H x V)                                  | 100° x 8°   |                       |
| Transducers  | LF 10 x 3.3" (84 mm) coated paper cone<br>HF 1 x 1" (25 mm) soft dome |                       |
| Continuous Power Handling @ Nominal Impedance <sup>3</sup> | 28V   | 100W @ 8Ω (400W peak) |
| Nominal Sensitivity @ 1m <sup>4</sup>                      | @ 1W<br>99 dB   | @ 2.83V<br>99dB       |
| Nominal Maximum SPL @ 1m <sup>5</sup>                      | Peak<br>125 dB  | Continuous<br>119 dB  |
| Transformer  | 70V: 100W, 50W, 30W, 20W<br>100V: 100W, 60W, 40W                      |                       |
| Recommended Amplifiers                                     | 100W - 200W @ 8Ω (28V - 40V)  |                       |

### APPLICATIONS

Houses of Worship · Retail Outlets · Hotels  
Bars and Restaurants · Courtrooms ·  
Auditoria · Theaters · Museums · Airports  
Corporate Meeting Rooms

### DESCRIPTION

The Desono COLW101 two-way 10 x 3.3" column loudspeaker is an excellent choice when sonic clarity and predictable directional control are required from an unobtrusive loudspeaker designed to blend in with the background.

The highly-focused dispersion pattern and improved speech intelligibility of the COLW101 enables it to excel in reverberant environments like houses of worship and auditoria, while it's weather-resistant construction allows it to be used in outdoor applications such as patios or concourses

The COLW101 utilizes a 4-position switchable transformer ranging from 20W to 100W with low-impedance bypass for constant-voltage operation, making it an excellent choice for large areas of BGM.

The Desono COLW101 is an excellent choice for both indoor and outdoor distributed audio applications that need speech intelligibility and background

### PHYSICAL

|                        |   |
|------------------------|---|
| Input Connection       | Multi-position pass-through, screw-down terminal block                        |
| Controls               | None; select transformer tap or low impedance input via terminal block wiring |
| Mounting Provisions    | Adjustable tilt L-bracket   |
| Environmental          | IP66 per IEC 60529  |
| Dimensions H x W x D   | 46.5" x 3.9" x 3.3" (1180 mm x 100 mm x 83 mm)                                |
| Weight                 | 17 lbs (7.7 kg)   |
| Finish                 | Refer to the Technical Drawings (page 3)                                      |
| Accessories (included) | L-brackets and 2x IP66 water-tight gland nuts                                 |

### OPTIONS

|             |                                    |
|-------------|------------------------------------|
| Accessories | COLWBRA: pan/tilt mounting bracket |
|-------------|------------------------------------|


*Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.*

*Data presented on this spec sheet represents a selection of the basic performance specifications for the model. These specifications are intended to allow the user to perform a fair, straightforward evaluation and comparison with other loudspeakers. For a detailed analysis of this loudspeaker's performance, please download the GLL file and/or the CLF file from our website: [biamp.com](http://biamp.com)*


# DESONO COLW101

TWO-WAY 10 x 3.3-INCH  
COLUMN LOUDSPEAKER


## AXIAL SENSITIVITY<sup>6</sup> (dB SPL)




## HORIZONTAL OFF-AXIS RESPONSE<sup>7</sup> (dB)




## IMPEDANCE (Ohms)




## VERTICAL OFF-AXIS DOWN RESPONSE<sup>7</sup> (dB)



## BEAMWIDTH<sup>8</sup> (Degrees)



## DIRECTIVITY INDEX<sup>9</sup> (dB)



<sup>1</sup> All measurements are taken indoors using a time windowed and processed signal to eliminate room effects, approximating an anechoic environment. All acoustic specifications are rounded to the nearest whole number. An external DSP using settings provided by Biamp is recommended to achieve further performance gains.

<sup>2</sup> The frequency range in which the on-axis processed response remains within 10dB of the average SPL.

<sup>3</sup> Maximum continuous input voltage (and the equivalent power rating, in watts, at the stated nominal impedance) that the system can withstand, without damage, for a period of 2 hours using an EIA-426-B defined spectrum; with recommended signal processing and protection filters.

<sup>4</sup> Averaged SPL over the operating range with an input voltage that would produce 1 watt at the nominal impedance and the averaged SPL over the operating range with a fixed input voltage of 2.83V, respectively; swept sine wave axial measurements with no external processing applied in whole space, except where indicated.

<sup>5</sup> Calculated based on nominal / peak power handling, respectively, and nominal sensitivity; exclusive of power compression.

<sup>6</sup> The on-axis variation in acoustic output level with frequency for a 1 watt swept sine wave, referenced to 1 meter with no signal processing. 1/6 octave Gaussian smoothing applied.

<sup>7</sup> The loudspeaker's magnitude response at various angles off-axis, with recommended signal processing applied in the operating mode which utilizes the largest number of individually amplified pass bands. 1/6 octave Gaussian smoothing applied.

<sup>8</sup> The angle between the -6dB points in the polar response of the loudspeaker when driven in the operating mode which utilizes the largest number of individually amplified pass bands. 1/6 octave Gaussian smoothing applied.

<sup>9</sup> The ratio of the on-axis SPL squared to the mean squared SPL at the same distance for all points within the measurement sphere for each given frequency; expressed in dB. 1/6 octave Gaussian smoothing applied.

# DESONO COLW101

TWO-WAY 10 x 3.3-INCH  
COLUMN LOUDSPEAKER

## TECHNICAL DRAWING / DIMENSIONS / FINISH

**H x W x D**  
46.5" x 3.9" x 3.3"  
(1180 mm x 100 mm x 83 mm)

**Unit Weight**  
17 lbs (7.7 kg)

**Shipping Weight**  
19.2 lbs (8.7 kg)

**Grille:**  
Aluminum  
White (RAL 9016) finish

**Enclosure / Finish**  
Aluminum, matte finish, White

