

SHURE

SLXD2+ DIGITAL WIRELESS HANDHELD TRANSMITTER

SPECIFICATIONS

(SUBJECT TO CHANGE)

Battery Type	Rechargeable Li-Ion or 1.5 V AA batteries
Dimensions (Dia. x L)	1.46 x 6.93 in (37.1 x 176 mm)
Weight	5.1 oz. (144 g)
Housing	Aluminum

AUDIO INPUT

Configuration	Unbalanced
Maximum Input Level	8.2 dBV (2.57 Vrms, 7.27 Vpp) <i>Note: Dependent on Microphone Type</i>

RF OUTPUT

Antenna Type	Integrated Single-Band Helical
Occupied Bandwidth	<200 kHz
Modulation Type	Shure Proprietary Digital
Power	1 mW/10 mW Varies by region. <i>See Frequency Range and Output Power Table</i>

MICROPHONE OPTIONS SEE SHURE.COM FOR MORE

SLXD2+/58	SLXD2+ Handheld Transmitter with SM58 Cardioid Capsule
SLXD2+/58S	SLXD2+ Handheld Transmitter with Beta 58A Supercardioid Capsule
SLXD2+/B87A	SLXD2+ Handheld Transmitter with Beta 87A Supercardioid Capsule
SLXD2+/B87C	SLXD2+ Handheld Transmitter with Beta 87C Cardioid Capsule
SLXD2+/58M6	SLXD2+ Handheld Transmitter with SM66 Cardioid Capsule
SLXD2+/N8	SLXD2+ Handheld Transmitter with Nexadyne 8/C Cardioid Capsule
SLXD2+/K8	SLXD2+ Handheld Transmitter with KSM8 Cardioid Capsule

OVERVIEW

The SLXD2+ handheld transmitter unlocks a new world of hands-free oversight and management for seasoned volunteers and pro engineers alike. Delivering wireless excellence, wherever required, wide-tuning SLXD+ transmitters and receivers stay in sync courtesy of a dedicated ShowLink® Ease control link. Manage interference, scan for new channels and update for clear transmission automatically. Also monitor and configure via a paired mobile device.

FEATURES

- Transparent 24-bit digital audio quality with >118 dB dynamic range
- Rock solid RF with 138 MHz wide-tuning range for greater geographical coverage:
 - > Up to 11 simultaneous systems in 6 MHz TV bands
 - > Up to 14 simultaneous systems in 8 MHz TV bands
- Automatic Setup - once linked, SLXD+ receivers and transmitters stay connected, despite any RF interference
- With ShowLink® Ease, transmitter parameters can be adjusted remotely over the air from the linked receiver, including:
 - > Changing the transmitter frequency once open frequency is identified
 - > Adjust transmitter gain
 - > Lock and unlock transmitter controls
 - > Transmitter firmware updates
- Monitor RF status and control receiver and transmitter parameters with Wireless Workbench desktop software, or remotely with the WWB Mobile app over Wi-Fi or Bluetooth
- Each SLXD+ component and system ships with AES-256 Encryption installed, f or complete and secure peace of mind
- Up to 8 hours of use from either 2 AA batteries (included) or optional Shure SB903 Li-Ion rechargeable batteries and charging accessories
- Rugged metal construction



SLXD2+/58
Digital Wireless
Handheld Transmitter