

SHURE

SLXD1+ DIGITAL WIRELESS BODYPACK TRANSMITTER

SPECIFICATIONS

(SUBJECT TO CHANGE)

Battery Type	Rechargeable Li-Ion or 1.5 V AA batteries
Dimensions (H x W x D)	3.86 x 2.68 x 1.0 in (98 x 68 x 25.5 mm)
Weight	3.1 oz (89 g)
Housing	PC/ABS

AUDIO INPUT

Connector	4-Pin male mini connector (TAM)
Configuration	Unbalanced
Impedance	1 MΩ
Maximum Input Level	8.2 dBV (2.57 Vrms, 7.27 Vpp)
Preamplifier Equivalent Input Noise (EIN)	-118 dBV

RF OUTPUT

Antenna Type	1/4 Wave
Occupied Bandwidth	<200 kHz
Modulation Type	Shure Proprietary Digital
Power	1 mW/10 mW Varies by region. See Frequency Range and Output Power Table.

MICROPHONE OPTIONS SEE SHURE.COM FOR MORE

WL185m	Cardioid Condenser Lavalier Microphone
WL93	Omnidirectional Miniature Condenser Microphone
MX153	Microflex® Headworn Earset Microphone
SM35	Cardioid Performance Headworn Microphone
WA305	1/4" Locking Instrument Cable

OVERVIEW

The SLXD1+ bodypack transmitter unlocks a new world of hands-free oversight and management for seasoned volunteers and pro engineers alike. Delivering wireless excellence, wherever required, wide-tuning SLXD+ transmitters and receivers stay in sync courtesy of a dedicated ShowLink® Ease control link. Manage interference, scan for new channels and update for clear transmission automatically. Also monitor and configure via a paired mobile device.

FEATURES

- Transparent 24-bit digital audio quality with >118 dB dynamic range
- Rock solid RF with 138 MHz wide-tuning range for greater geographical coverage:
 - > Up to 11 simultaneous systems in 6 MHz TV bands
 - > Up to 14 simultaneous systems in 8 MHz TV bands
- Automatic Setup – once linked, SLX-D+ receivers and transmitters stay connected, despite any RF interference
- With ShowLink® Ease, transmitter parameters can be adjusted remotely over the air from the linked receiver, including:
 - > Changing the transmitter frequency once open frequency is identified
 - > Adjust transmitter gain
 - > Lock and unlock transmitter controls
 - > Transmitter firmware updates
- Monitor RF status and control receiver and transmitter parameters with Wireless Workbench desktop software, or remotely with the WWB Mobile app over Wi-Fi or Bluetooth
- Each SLX-D+ component and system ships with AES-256 Encryption installed, for complete and secure peace of mind
- Up to 8 hours of use from either 2 AA batteries (included) or optional Shure SB903 Li-Ion rechargeable batteries and charging accessories
- Ergonomic and durable plastic construction



SLXD1+
Digital Wireless
Bodypack Transmitter