

SYSTEMS AND CONTROL / VOICE ALARM EN 54 / CHARGER AND BATTERIES

SMART-PSM48

POWER SUPPLY MANAGER



ESPECIALLY RECOMMENDED IN:



All sectors



+ Info:
<https://fonestar.com/SMART-PSM48>

DESCRIPTION

Public address and voice alarm system power supply equipment

TECHNICAL CHARACTERISTICS

FEATURES	Power supply manager Manages PS power supplies with a maximum of 60 A. Includes the management of the backup batteries (up to 200 Ah). In reserve system supplies 3'2 kW (48 V). The unit complies with EN 54-4 standards and also with EN 12101-10 Heat and Smoke Control System. It can manage up to 4 SMART-PS power units and 4 AKU batteries in series.
INPUTS	4x SMART-PS power supplies. Threaded terminals 1 input for AKU batteries (VRLA 12 V 15-200 Ah). Threaded terminals
OUTPUTS	8x 48 V CC power supply. Threaded terminals (1 output max 30 A, 8 outputs max 63 A) Total maximum load 3.200 W
TEMPERATURE	Operation: -5° ~ +40°C
POWER SUPPLY	230 V CA 50/60 Hz, 885 W Fuse: 3'85 A
DIMENSIONS	482 x 85 x 443 mm depth
WEIGHT	7'2 kg



+ Info:

<https://fonestar.com/SMART-PSM48>