

## TECHNICAL SPECIFICATIONS



### iLive 2

**iLive 2 handheld antenna diversity wireless microphone system with 32 selectable channels with automatic channel targeting and synchronization.**

The microphone signal receiver, handheld microphone transmitter and jack/jack cable are included in each set. Advanced design PCB and excellent quality metal body handheld microphone transmitter equipped with dynamic cardioid microphone capsule makes these sets very universal for use on stage and in the conference rooms.

	<b>iLive 2 receiver</b>
Power supply	12-15 V DC, 1.25 A
Output	Balanced XLR , unbalanced 6,3 mm TS JACK
Receiver way	Two frequency conversion super-heterodynes
Intermediate frequency	10,7 MHz
Antenna	BNC
T.H.D	< 0,7 %
Sensitivity	6 dB $\mu$ V
Image rejection	36 dB
Max. audio output	0 dB
Dimensions (H x W x D)	45 mm x 210 mm x 206 mm
Weight	1.4 kg
Material	Steel enclosure, aluminum front panel
	<b>iLIVE 2 handheld transmitter</b>
Carrier frequency range	606 MHz - 621 MHz
Modulation	FM
Channels	32
Audio frequency response	45 Hz - 18 kHz
S/N ratio	> 105 dB
Anntena	Built-in spiral antenna
Transmitter's power	15 mW
Working range	60 m (Note: actual range depends on RF signal absorption, reflection, and interference)
Polar pattern	Cardiod
Dimensions (H x W x D)	240 mm (lenght)
Weight	302 g
Material	Aluminum